	Type	L #	Hits	Search Text	DBs
1	BRS	L4	*kwic* (52)	@ad<"20010104" and (download$3 same software) and (authoriz$5 same software) and (hardware near3 (id identification))	US-PGPUB; USPAT; EPO; JPO; IBM_TDB
2	BRS	L1	*kwic* (38)	(software adj3 (id identification)) same (hardware adj3 (id identification)) same (function hash$3 concatenat$3 combin$5)	US-PGPUB; USPAT; EPO; JPO; IBM_TDB
3	BRS	L2	*kwic* (56)	((software adj3 (id identification)) and (hardware adj3 (id identification)) and (transfer$5 transmit$5 download$3 updat$3 upgrad$3 install$5)) and "713"/$.ccls.	US-PGPUB; USPAT; EPO; JPO; IBM_TDB
4	BRS	L3	*full* (16)	(((software adj3 (id identification)) and (hardware adj3 (id identification)) and (transfer$5 transmit$5 download$3 updat$3 upgrad$3 install$5)) and "713"/$.ccls.) and @ad<"20010104"	US-PGPUB; USPAT; EPO; JPO; IBM_TDB
5	BRS	L5	*ABS + kwic* (30)	@ad<"20010104" and (authoriz$5 same receiv$3 same (upgrad$3 updat$3)) and (hardware near2 (serial id identification))	US-PGPUB; USPAT; EPO; JPO; IBM_TDB

	Type	L #	Hits	Search Text	DBs
6	BRS	L6	*full* (11)	(@ad<"20010104" and (717/173.ccls.)) and ((serial adj3 number) (hardware adj4 (id identification)))	US-PGPUB; USPAT; EPO; JPO; IBM_TDB
7	BRS	L7	*ABS only* (2)	newell.in. and laufer	US-PGPUB; USPAT; EPO; JPO; IBM_TDB
8	BRS	L9	*full* (17)	@ad<"20010104" and ((receiv$3 download$3) same (software) same (updat$3 upgrad$3) same password same identification)	US-PGPUB; USPAT; EPO; JPO; IBM_TDB
9	BRS	L10	*full* (24)	@ad<"20010104" and (download$3 same software) and (authoriz$5 same (transfer$4 copy$3 download$3) same software) and (hardware near3 (id identification (serial adj number) (SIM)))	US-PGPUB; USPAT; EPO; JPO; IBM_TDB
10	BRS	L11	*ABS + full* (12)	@ad<"19980918" and ((smart adj card) with key) and ((back adj up) with key)	US-PGPUB; USPAT; EPO; JPO; IBM_TDB

	Type	L #	Hits	Search Text	DBs
11	BRS	L12	*DBS* (42)	@ad<"20010104" and (((key password) near3 (function based)) near3 ((number near3 (downloads copies))))	US-PGPUB; USPAT; EPO; JPO; IBM_TDB
12	BRS	L8	*title scan* (22?)	@ad<"20010104" and (((key password) near3 (function based)) same ((number near3 (downloads copies))))	US-PGPUB; USPAT; EPO; JPO; IBM_TDB